

**LZW31-SN**

# **Instructions**

# Next Gen Smart Lighting

We're excited to have you on this journey with us and we're here for you every step of the way. Not only are we smart home owners ourselves, but we build all of our products alongside 1,000's of passionate community members. To see how the project came to life and how everyone contributed, please see Page 70 or visit: [inov.li/lightsout](http://inov.li/lightsout). It's truly amazing working with people of all walks of life and even more humbling to see everyone's dedication to making some of the best smart home products.

Thank you so much for your trust in us and welcome to the next generation of smart lighting with Inovelli.

Eric H. - Founder/CEO

Eric M. - Founder/CTO

Handwritten signatures of Eric H. and Eric M. in black ink. Eric H.'s signature is on the left, and Eric M.'s signature is on the right.

# Table of Contents

|                         |    |  |    |
|-------------------------|----|--|----|
| Quick Setup & Inclusion | 05 | Advanced Features                                    | 43 |
| Wiring                  | 11 | Switch Parameters                                    | 45 |
| Warnings                | 14 | Other Advanced Features                              | 46 |
| Vocabulary              | 21 | Z-Wave™ Information                                  | 47 |
| Steps 1-4               | 22 | Product & Contact Info                               | 63 |
| Step 5 - Installation   | 30 | FCC/IC Info  | 65 |
| Manual Setup            | 31 | Product Info   | 68 |
| Example                 | 33 | Contact/Warranty Info                                | 69 |
| AC Type & Switch Mode   | 34 | Project Lights Out                                   | 70 |
| Hub/Gateway Setup       | 37 |  |    |
| SmartThings             | 39 | For the most recent                                  |    |
| Home Assistant          | 40 | instructions visit:                                  |    |
| Hubitat                 | 41 | <a href="http://inov.li/lzw31sn">inov.li/lzw31sn</a> |    |

# Navigating this Manual

We designed this manual as if we were installing the switch ourselves. We suggest reviewing the full manual before beginning the installation process. There are five areas this manual covers:

1. Getting to know your switch
2. Figuring out your wiring
3. Manually connecting your switch (after wiring installation)
4. Connecting to your hub/gateway
5. Configuring your switch (optimize the settings)

As we continue to work with hub manufacturers, and improve our products. It may be necessary to periodically update this manual. You can always find the latest version of this manual by visiting: [inov.li/lzw31sn](http://inov.li/lzw31sn)

Reprinted - 2023.09.29

**Quick Setup & Inclusion.**

# Quick Setup Notes

We get it, you're ready to go. No need to flip through the manual, you want the abridged version. **This section assumes you have your switch wired correctly and the blue LED Bar is lit up.**

It also assumes you know how to enter the Z-Wave pairing mode on your hub/gateway (and have a Z-Wave compatible hub/gateway).


To see which hubs are compatible, please visit: [inov.li/lzw31snhubs](http://inov.li/lzw31snhubs)

While these instructions likely won't change, for the most up-to-date instructions, we recommend visiting: [inov.li/lzw31snQS](http://inov.li/lzw31snQS)

# Including Your Switch

**Auto-Pairing:** The switch will start the inclusion process when the config button (C) is pressed three times consecutively. To indicate the switch is in inclusion mode, the LED Bar (D) will pulse blue. Once the switch is in inclusion mode, start the Z-Wave inclusion process on the hub at any time. If successful, the LED Bar (D) will flash green.

If the switch is unsuccessful during inclusion, you can exclude (reset) the switch by putting your gateway in exclusion mode and pressing the config button (C) three times. The LED Bar (D) will pulse blue and then flash green if successful or red if not. After exclusion, you can try inclusion again.



# Getting to Know Your Switch

Please use the next couple pages to get to know your smart switch.

**A. Light On / Increase Dim % Level:** Tap 1x to turn on your light or hold to increase the brightness level (dim percentage). In addition, it can be used to activate scene control (multi-taps and holds) where up to 7 scenes can be added\*.

**B. Light Off / Decrease Dim % Level:** Tap 1x to turn off your light or hold to decrease the brightness level (dim percentage). In addition, it can be used to activate scene control (multi-taps and holds) where up to 7 scenes can be added\*.


**C. Config / Favorites Button:** Used to configure certain



parameters of the switch. In addition, it can be used to activate scene control (multi-taps and holds) where up to 1 scene can be added\*.

**D. RGB LED Bar:** Multi-functional LED bar that shows the % level at which your switch is at. In addition, it can be used as a notifier\* for various events (ie: turn red when alarm is armed, pulse purple if garage is left open, etc).

**E. Air Gap:** This can be pulled out to cut power to the load and is there for safety purposes.



\* Hub must support these features. Please see pg. 46.

Page intentionally left blank.

**Wiring.**

# Wiring Notes

Due to the number of ways these switches can be wired, all schematics are housed online and you can access the schematics by visiting: [inov.li/lzw31snwiring](http://inov.li/lzw31snwiring)

To work your way through this section, first read the warnings, then familiarize yourself with the vernacular used. Finally, keep notes as you go through the first three (3) steps as you will use them to determine whether or not your wiring is compatible and whether or not you have to manually setup your switch (pg. 31).

Finally, please do not attempt to install these switches if you are unfamiliar with electrical as serious injury can occur.

# Safety Reminder

Consult a qualified electrician if necessary as **we are unable to give wiring advice outside of schematics.**

If you are unsure how electrical circuits work, please do not try installing this device. As exciting as it is to have a smart switch installed, it can be dangerous and even life-threatening if you do not install it correctly. Improper installation will void the product's warranty.

Please read through the warnings on the next few pages before installing your switch. We can't stress enough how dangerous installation can be if you don't know what you're doing.

# Warnings

**Caution - Please Read:** This device (LZW31-SN) is intended for installation in accordance with the National Electric Code and local regulations in the United States, or the Canadian Electrical Code and local regulations in Canada. If you are unsure or uncomfortable about performing this installation consult a qualified electrician. This product is made for indoor use only and is not designed or approved for use on power lines other than 120VAC, 60Hz, single phase. Attempting to use this LZW31-SN on non-approved power lines may have hazardous consequences.

**Attention - Information importante:** Cet appareil (LZW31-SN) est conçu pour être installé conformément au « National Electric Code » et aux réglementations locales aux

États-Unis, ou au Code canadien de l'électricité et aux réglementations locales canadiennes. Si vous ne vous sentez pas à l'aise ou qualifiés pour effectuer cette installation, veuillez consulter un électricien qualifié. Ce produit est conçu pour une utilisation intérieure uniquement et n'est pas conçu ou approuvé pour une utilisation avec une ligne électrique ayant un voltage autre que 120 VCA, 60 Hz, monophasé. L'utilisation du LZW31-SN avec une ligne électrique non approuvée peut avoir des résultats dangereux.

**Other Warnings:** Risk of Fire, Electrical Shock & Burns

**Autres avertissements:** Risque d'incendie, de choc électrique et de brûlures

# Warnings (Continued)

**Recommended Installation Practices:** Use only indoors or in an outdoor rated box. Turn off the circuit breaker. Installing this switch and module with the power on will expose you to dangerous voltages. Connect only copper or copper-clad wire to the switch or module.

To reduce the risk of overheating and possible damage to other equipment, do not install to control a receptacle, a motor-operated appliance, a fluorescent lighting fixture or a transformer supplied appliance and do not use the LZW31-SN load output to control no more than indicated.

Dimming an inductive load (by connecting to the light load wire),

- 400 Watts (Incandescent)
- 300 Watts (LED)
- 150 Watts (CFL)

The above assumes no heat sink tabs are removed. If you are removing the heat sink tabs, please see max wattage specs on page 68.



such as a fan or transformer, appliance, motor or any device not specifically designed for dimming, could cause damage to the dimmer, the load bearing device, or both. To install your Dimmer Switch (LZW31-SN), you'll need to identify the following four wires (NOTE: Neutral is not mandatory, but recommended):

- **Line:** Usually black and can also be called the, "hot" or "live" and carries 120VAC electricity into the electrical box
- **Neutral\*:** Usually white and is commonly daisy chained from box to box, usually appearing as a white wire bundle.
- **Load:** Usually black, blue or red
- **Ground:** Bare copper wire or metal fixture (if grounded)

\* Neutral is mandatory in certain installations. See page 29 for additional details.

# Warnings (Continued)

If you are having difficulties identifying wires, please consult an electrician.

**Pratiques d'installation recommandées:** Utiliser uniquement à l'intérieur ou à l'extérieur dans une boîte adaptée aux conditions extérieures. Éteignez le disjoncteur. L'installation de cet interrupteur et de ce module alors que le courant est allumé vous exposera à des tensions dangereuses. Connectez uniquement un fil de cuivre ou gainé de cuivre au commutateur ou au module.

Pour réduire le risque de surchauffe et d'endommager d'autres équipements, il est important de connecter des lumières incandescentes ayant moins de 600 watts, des lumières DEL ayant moins de 300 watts, des ampoules fluocompactes ayant moins de 150

watts ou un ventilateur utilisant moins de 1 ampère et ce dernier avec l'interrupteur en mode marche/arrêt uniquement.

La gradation d'une charge inductive, comme un ventilateur ou un transformateur, pourrait endommager le gradateur, l'interrupteur ou les deux appareils. Veuillez régler l'interrupteur en mode marche/arrêt si vous utilisez un ventilateur.

Pour installer votre variateur (LZW31-SN), vous devrez identifier les quatre fils suivants (REMARQUE : le neutre n'est pas obligatoire, mais recommandé) :

- **Ligne:** généralement noire et peut également être appelée « chaud » ou « sous tension » et transporte l'électricité 120 VCA

# Warnings (Continued)

dans le boîtier électrique

- **Neutre:** habituellement blanc et connecté en série d'une boîte à l'autre, les fils sont habituellement attachés ensemble dans la boîte électrique
- **Charge:** habituellement noire, bleue ou rouge
- **Mise à terre:** fil de cuivre nu ou boîtier métallique (si celui-ci est mis à la terre)

Si vous rencontrez des difficultés à identifier les fils, veuillez consulter un électricien.

**Équipement médical:** Veuillez ne pas utiliser cet interrupteur pour contrôler de l'équipement médical ou nécessaire à la survie. Les appareils Z-Wave ne doivent jamais être utilisés pour contrôler la marche or l'arrêt d'équipement médical et/ou nécessaires à la survie.

# Vocabulary

Before we go into actual steps, it's important to be familiar with the vernacular used on the following pages. Please see below:

- **Line:** This is your hot wire (120V) - aka: "live" wire
- **Load:** This is the wire that runs from your light switch to what you're controlling (ie: bulb(s), fan, etc)
- **Neutral:** This is the wire that carries current back to the power source (you may not have this in your house)
- **Single-Pole:** One switch controlling one or more load(s)
- **Multi-Way:** Refers to 3-Way (2 switches, 1 load), 4-Way (3 switches, 1 load), or 5-Way setups (4 switches, 1 load)
- **Toggle ("Dumb") Switch:** Refers to your existing switch (ie: the switch(es) you had before replacing with your smart switch(es))
- **Aux Switch:** Refers to the Inovelli Aux Switch ([inov.li/aux](http://inov.li/aux))

# Step 1 - Determine Wiring Type

The first step is to determine how many switches control your load(s) (aka: light(s)).


Using the diagram on the next page, please determine what your wiring type is and remember this selection:

- **Single-Pole:** One switch controls one load (load may contain more than one light, etc).
- **Multi-Way:** Two or more switches control one load (load may contain more than one light, etc). We will use the term, "multi-way" instead of 3-Way, 4-Way, 5-Way, etc as the programming of the switch is the same regardless.




## Single-Pole

One switch controls one (or more) load(s).



## Multi-Way

Two or more switches control one (or more) load(s).



# Step 2 - Determine Switch Layout

**NOTE:** If you determined in Step #1 that your switch is single-pole, you can skip this step. This step is for multi-way setups only.

Using the diagram on the next page, please determine what your wiring layout is and remember this selection:

- **Smart Switch + Toggle Switch:** One smart switch and one (or more) toggle/existing switch (one already in your wall).
- **Smart Switch + Aux Switch:** One smart switch and one (or more) aux/add-on switch (Model #: AUX01 or [inov.li/aux](http://inov.li/aux)).
- **Smart Switch + Smart Switch:** Two (or more) smart switches.

See [inov.li/lzw31snlayout](http://inov.li/lzw31snlayout) for the pro/cons of each setup. You may not mix/match (ie: Smart + Aux + Toggle) in the same circuit.

**Switch Layout (Circle One):** Toggle, Aux, or Smart Switch(es)





### **Smart + Toggle Switch**

One Inovelli smart switch & one (or more) toggle/existing switch.



### **Smart + Aux Switch**

One Inovelli smart switch & one (or more) Inovelli aux switch (AUX01).



### **Smart Switches**

Two (or more) Inovelli smart switches.


# Step 3 - AC Power Type

In this step, we will determine if you have a neutral wire, which is typically white and located in the back in your switch gang-box (typically in a bundle of wires tied together).

Here are some signs you may have a neutral wire:

- If your house was built in the mid-1980's or later
- If there is an outlet (receptacle) near the switch
- If switches are in the same gang-box (regardless of the year your house was built)

See the next page for details on checking for a neutral wire.



After turning off your breaker, pull out the switches (**WARNING:** there may be multiple circuits in one gang-box -- please ensure all circuits are turned off). Check the back of your gang-box for a bundle of white wires. These are typically neutrals.

# Step 4 - Compatibility Check

In this step, we will determine if your switch can be installed with your current wiring setup. If not, you can see some alternate solutions on how to accomplish compatibility.

Taking the answers you circled in Steps 1-3, please see the chart on the next page to see if your switch is compatible with your setup.

**Example:** If you circled, "Multi-Way", "Toggle Switch" and "Neutral", you will see that your wiring is compatible. However, if you circled, "Multi-Way", "Toggle Switch" and "No Neutral", you will see that your wiring is not compatible and you will need to purchase an auxiliary switch ([inov.li/aux](http://inov.li/aux)).

| Wiring Type           | Switch Layout   | Power Type | Supported |
|-----------------------|-----------------|------------|-----------|
| Single-Pole           |                 | Neutral    | Yes       |
|                       |                 | No Neutral | Yes       |
| Multi-Way<br>(3+ Way) | Toggle (Switch) | Neutral    | Yes       |
|                       |                 | No Neutral | No        |
|                       | Aux (Switch)    | Neutral    | Yes       |
|                       |                 | No Neutral | Yes       |
|                       | Smart (Switch)  | Neutral    | Yes       |
|                       |                 | No Neutral | No        |

**IMPORTANT:** For installations where no neutral wire is present, you will need to install a special bypass to prevent flickering and/or keep your switch powered. Bypasses can be purchased here: [inov.li/bypass](http://inov.li/bypass)

# Step 5 - Switch Installation

The last step is to physically install your switch. After you've determined your wiring type, switch layout, AC Power type and whether or not you have a compatible setup, it's time to look at the wiring schematics and install your switch.

As mentioned, there are many different ways your switch can be wired that if we posted them here, we'd have an encyclopedia of a manual, so all of our schematics are housed online. [UL specifies the tightening torque for the screws to be 0.8 N.m \(7.08 lbf-in\).](#)

Keep note of your answers from the prior steps and go to: [inov.li/lzw31snwiring](http://inov.li/lzw31snwiring) and match up your answers to the correct schematic section.

**Manual Setup.**

# Manual Setup Notes

NOTE: This is much easier to complete once your switch is paired to your hub. You can skip this step if you have a hub capable of changing parameters or you are using this in a neutral/single-pole setting.

Since this switch has so many different available configurations (aux, toggle, neutral, non-neutral, etc), you may need to manually program the switch to work.

Luckily, it's as simple as pressing a couple buttons. Feel free to follow the steps on the next couple of pages or visit:  
[inov.li/lzw31snmanualsetup](http://inov.li/lzw31snmanualsetup)

Again, if you are using this switch with a neutral wire and a single-pole setting, you can skip this section.



# Manual Setup Explanation

If your switch is installed without a neutral wire and/or you installed the switch in a multi-way (3-Way, 4-Way, etc) setup, you will need to program the switch to tell it to work properly.

We've created ways to do this directly at the switch, however, we recommend you do this once the switch is paired to the hub as it's much easier to change the parameters via your hub user interface.

However, in the event that you do not have access to a hub, please follow the instructions on pages 34-36.

# Non-Neutral Mode

To put your switch into non-neutral mode, please follow the directions below.

- Hold down the configuration button for 10-15 seconds until the LED Bar turns yellow and let go
- Tap the configuration button 12x -- the LED Bar should long flash yellow 1x and then fast flash 2x
- Tap 1x on the bottom paddle (off part) -- the LED Bar should remain blank
- Hold down on the configuration button for 10-15 seconds until the LED Bar turns yellow and let go -- it should blink cyan to confirm the setting was saved

# Aux Mode

To program your switch to work with an auxiliary switch, please follow the directions below.

- Hold down the configuration button for 10-15 seconds until the LED Bar turns yellow and let go
- Tap the configuration button 13x -- the LED Bar should long flash yellow 1x and then fast flash 3x
- Tap 2x on the top paddle (on part) -- the LED Bar should fast flash 2x
- Hold down on the configuration button for 10-15 seconds until the LED Bar turns yellow and let go -- it should blink cyan to confirm the setting was saved

# Dumb/Existing Switch Mode

To program your switch to work with your dumb/existing switch, please follow the directions below.

- Hold down the configuration button for 10-15 seconds until the LED Bar turns yellow and let go
- Tap the configuration button 13x -- the LED Bar should long flash yellow 1x and then fast flash 3x
- Tap 1x on the top paddle (on part) -- the LED Bar should fast flash 1x
- Hold down on the configuration button for 10-15 seconds until the LED Bar turns yellow and let go -- it should blink cyan to confirm the setting was saved

**Hub/Gateway Setup.**

# Hub/Gateway Setup Notes

As manufacturers update their hub/gateway platforms, the setup process may change. We recommend checking our website for the latest directions, by visiting the relevant short-links below.

If you don't see your hub, please go to: [inov.li/lzw31sn0T](https://inov.li/lzw31sn0T)

## SmartThings

[inov.li/  
lzw31snST](https://inov.li/lzw31snST)

## Home Asst. Z-Wave JS

[inov.li/  
lzw31snZWJS](https://inov.li/lzw31snZWJS)

## Home Asst. Z-Wave JS UI

[inov.li/  
lzw31snZWJSUI](https://inov.li/lzw31snZWJSUI)


## Hubitat

[inov.li/  
lzw31snHE](https://inov.li/lzw31snHE)

# SmartThings Instructions

**COMPATIBLE HUBS:** Samsung SmartThings Hub V1, V2 and Samsung or Aeotec Hub V3 (NOTE: You will need to install an Edge Driver to ensure full functionality of the switch. For more info, please go to: [inov.li/lzw31snSTPrereqs](http://inov.li/lzw31snSTPrereqs)).

First, tap the Config Button (C) 3x until the LED Bar (D) pulses blue, then proceed to the instructions below:

- Open the SmartThings app and click on the devices icon 
- Tap on the (+) button and click, "Add Device"
- Click, "Scan nearby"
- If successful, the LED Bar (C) will turn green and your app will show the new switch (feel free to rename it)

# Home Assistant Instructions

**COMPATIBILITY:** We recommend either Z-Wave JS or Z-Wave JS UI (formerly Z-Wave JS2mqtt). NOTE: you will also need a compatible Z-Wave stick - a full list can be found here: Z-Wave JS = [inov.li/lzw31snZWJSsticks](https://inov.li/lzw31snZWJSsticks) or Z-Wave JS UI = [inov.li/lzw31snZWJSUIsticks](https://inov.li/lzw31snZWJSUIsticks)).

You didn't think we'd be able to fit the HA instructions in here, did you?! Please visit our website :)

**Z-Wave JS Instructions**

[inov.li/lzw31snZWJS](https://inov.li/lzw31snZWJS)

**Z-Wave JS UI Instructions**


[inov.li/lzw31snZWJSUI](https://inov.li/lzw31snZWJSUI)



# Hubitat Instructions

**COMPATIBLE HUBS:** Hubitat C3, C4, C5 and C7 (NOTE: You may need to install a Device Driver to ensure full functionality of the switch. We recommend doing this prior to pairing. For more info, please go to: [inov.li/lzw31snHEPrereqs](http://inov.li/lzw31snHEPrereqs)).

First, tap the Config Button (C) 3x until the LED Bar (D) pulses blue, then proceed to the instructions below:

- Login to your Hubitat portal and click on the devices tab  Devices
- Tap on the (+) Add Device button and click, "Z-Wave" under, "Add device manually"
- Click, "Start Z-Wave Pairing" and your hub should go into pairing mode, find and initialize the device
- If successful, the LED Bar (D) will turn green and your app will show the new switch (feel free to rename it)

Page intentionally left blank.

**Advanced Features.**

# Advanced Features Notes

**NOTE:** The advanced features shown below are what is built into the switch firmware, and may or may not be supported by your hub/gateway. We've confirmed they're supported on SmartThings, Hubitat, and Home Assistant.

These switches are packed with a ton of amazing features, which include scene control (multi-tap), animated notifications, smart bulb mode, energy monitoring, and approximately 20 different parameters to customize your switch.

The manual does not have enough room to list out and explain all the parameters and advanced features. However, the following pages will direct you to the proper URL's. An overview can be found at the following URL: [inov.li/lzw31snAF](http://inov.li/lzw31snAF)

# Switch Parameters

There are approximately 20 different parameters on this switch, making it one of the most customizable switches out there.

They can be found on Page 53 in this manual or by visiting:  
[inov.li/lzw31snparameters](http://inov.li/lzw31snparameters)

Some of the highlights include: changing the dimming speed, multi-tap speed, min/max brightness, LED bar color, power/energy monitoring reporting, default dim level, and so much more.

If your hub does not support parameter changes, you can program a lot of these directly from the configuration button. Please visit:  
[inov.li/lzw31snLC](http://inov.li/lzw31snLC)

# Other Advanced Features

To setup some of the other advanced features, such as: Animated Notifications, Scene Control, Smart Bulb Mode and Z-Wave Associations, please see the URL's below as the instructions will be different depending on the hub you're using.

- **Animated Notifications:** [inov.li/lzw31snAN](http://inov.li/lzw31snAN)
- **Scene Control:** [inov.li/lzw31snSC](http://inov.li/lzw31snSC)
- **Smart Bulb Mode:** [inov.li/lzw31snSBM](http://inov.li/lzw31snSBM)
- **Z-Wave Associations:** [inov.li/lzw31snZA](http://inov.li/lzw31snZA)

As noted on page 45, your switch has the ability to program parameters from the configuration button. To learn more, please visit: [inov.li/lzw31snLC](http://inov.li/lzw31snLC)

**Z-Wave Information.**

# About Z-Wave & This Device

As mentioned in the beginning of the manual, we're all smart home owners ourselves and have an amazing community of people who are eager to help and share their setups.

If you ever run into any issues, please do not hesitate to submit a ticket, or post in the community. We'd love to hear from you.

**Community Link:** [inov.li/community](https://inov.li/community)

**Submit a Ticket:** [inov.li/support](https://inov.li/support) (or scan the QR Code below)

Thanks again for your support and we look forward to helping you get the most out of our smart home!



# DSK Location

The DSK information required for some inclusion methods can be found either on the product (QR Code located at the bottom front-left of the switch), or on the back of the box at the bottom left (QR Code located at the bottom right). Please keep this in a safe space or write it down for your records.

# Z-Wave Association Groups

| Grouping Identifier | Max Nodes | Send Commands                 |
|---------------------|-----------|-------------------------------|
| Group 1             | 5         | 1. Central Scene Notification |
|                     |           | 2. Basic Report               |
|                     |           | 3. Multilevel Report          |
|                     |           | 4. Protection Report          |
|                     |           | 5. Device Reset Locally       |
|                     |           | 6. Meter Report               |
| Group 2             | 5         | Basic Set                     |
| Group 3             | 5         | Switch Multilevel Set         |
| Group 4             | 5         | Switch Multilevel Set         |

### **Group 1: Lifeline**

Members of this group will receive unsolicited messages related to the status of the switch

### **Group 2: Basic Set**

Sends On & Off commands to associated devices

1. Single press on the up button sends BasicSet (0xFF)
2. Single press on the down button sends BasicSet (0x00)

### **Group 3: Switch Multilevel Set**

Sends Dim & Brighten commands to associated devices.

1. Hold & Release Up button sends SwitchMultiLevelSet
2. Hold & Release Down button sends SwitchMultiLevelSet

3. Single press Up button sends SwitchMultiLevelSet (0xFF)
4. Single press Down button sends SwitchMultiLevelSet (0x00)

#### **Group 4: Switch Multilevel Start/Stop**

Sends start / stop level change to associated devices

1. Hold Up button sends SW\_MULTILEVEL\_START\_LEVEL\_CHANGE
2. Release Up button sends SWITCH\_MULTILEVEL\_STOP\_LEVEL\_CHANGE
3. Hold Down button sends SW\_MULTILEVEL\_START\_LEVEL\_CHANGE
4. Release Down button sends SW\_MULTILEVEL\_STOP\_LEVEL\_CHANGE

# Z-Wave Parameters

As mentioned on page 45, there are over 20 parameters on this switch depending on the firmware version. An overview of the parameters can be found on pages 53 through 57, but the most up-to-date parameter documentation can be found on our website here: [inov.li/lzw31snparameters](http://inov.li/lzw31snparameters)

| # | Name                   | Range | Default | Size | FW Version |
|---|------------------------|-------|---------|------|------------|
| 1 | Dimming Speed (Local)  | 0-100 | 3       | 1    | 1.35+      |
| 2 | Dimming Speed (Remote) | 0-101 | 101     | 1    | 1.35+      |
| 3 | Ramp Rate (Local)      | 0-101 | 101     | 1    | 1.35+      |

| # | Name                     | Range   | Default | Size | FW Version |
|---|--------------------------|---------|---------|------|------------|
| 4 | Ramp Rate<br>(Remote)    | 0-101   | 101     | 1    | 1.35+      |
| 5 | Minimum Dim<br>Level     | 1-45    | 1       | 1    | 1.35+      |
| 6 | Maximum Dim<br>Level     | 55-99   | 99      | 1    | 1.35+      |
| 7 | Invert Switch            | 0-1     | 0       | 1    | 1.35+      |
| 8 | Auto-Off Timer           | 0-32767 | 0       | 2    | 1.35+      |
| 9 | Default Level<br>(Local) | 0-99    | 0       | 1    | 1.35+      |

| #  | Name                        | Range  | Default | Size | FW Version |
|----|-----------------------------|--------|---------|------|------------|
| 10 | Default Level (Remote)      | 0-99   | 0       | 1    | 1.35+      |
| 11 | Level After Power Restored  | 1-100  | 0       | 1    | 1.35+      |
| 13 | Default LED Color           | 1-255  | 170     | 1    | 1.35+      |
| 14 | Default LED Intensity (On)  | 0-10   | 5       | 2    | 1.35+      |
| 15 | Default LED Intensity (Off) | 0-10   | 1       | 1    | 1.35+      |
| 16 | LED Notification            | Varies | 0       | 4    | 1.35+      |

| #  | Name                              | Range   | Default | Size | FW Version |
|----|-----------------------------------|---------|---------|------|------------|
| 17 | LED Indicator Timeout             | 0-10    | 3       | 1    | 1.35+      |
| 18 | Active Power Reports              | 0-100   | 10      | 1    | 1.35+      |
| 19 | Periodic Power/<br>Energy Reports | 0-32767 | 3600    | 1    | 1.35+      |
| 20 | Active Energy Reports             | 0-100   | 10      | 2    | 1.35+      |
| 21 | AC Power Type                     | 0-1     | 1       | 1    | 1.35+      |
| 22 | Switch Type                       | 0-2     | 0       | 1    | 1.35+      |



| #  | Name                    | Range | Default | Size | FW Version |
|----|-------------------------|-------|---------|------|------------|
| 50 | Switch Delay Adjustment | 1-9   | 7       | 1    | 1.49+      |
| 51 | Switch Delay            | 0-1   | 1       | 1    | 1.47+      |
| 52 | Smart Bulb Mode         | 0-1   | 0       | 1    | 1.47+      |

# Security 2 Command Classes

| Command Class             | Version | Required Security Class |
|---------------------------|---------|-------------------------|
| Z-Wave Plus Info          | V2      | None                    |
| Switch Multilevel         | V4      | S0/S2                   |
| Configuration             | V4      | S0/S2                   |
| Central Scene             | V3      | S0/S2                   |
| Association               | V3      | S0/S2                   |
| Multi-Channel Association | V3      | S0/S2                   |
| Transport Service         | V2      | None                    |
| Version                   | V3      | S0/S2                   |
| Manufacturer Specific     | V2      | S0/S2                   |

| Command Class             | Version | Required Security Class |
|---------------------------|---------|-------------------------|
| Device Reset Locally      | V1      | S0/S2                   |
| Application Status        | V1      | S0/S2                   |
| Powerlevel                | V1      | S0/S2                   |
| Security 0                | V1      | None                    |
| Security 2                | V1      | None                    |
| Supervision               | V1      | None                    |
| Firmware Update Meta Data | V5      | S0/S2                   |
| Meter                     | V3      | S0/S2                   |
| Protection                | V2      | S0/S2                   |

# Manufacturer Compatibility

This product can be operated in any Z-Wave network with other Z-Wave certified devices from other manufacturers. All non-battery operated nodes within the network will act as repeaters regardless of vendor to increase reliability of the network. Each module is designed to act as a repeater, which will re-transmit a radio frequency (RF) signal by routing the signal around obstacles and radio dead spots to ensure that the signal is received at its intended destination. The Inovelli Red Series Dimmer Switch is a security enabled Z-Wave Plus™ device. A security enabled Z-Wave Plus controller must be used in order to fully utilize the product.

# Factory Reset / Exclusion Info

To factory reset your device, first, hold the Configuration / Favorites Button (C) for 20 seconds until the LED Bar (D) turns red and let go. The switch should blink red a few times indicating it has been factory reset. You may also use a certified Z-Wave controller to remove the device from your network to factory default. Only use these procedures in the event that the primary controller is missing or otherwise inoperable.

Exclusion will reset your device as well and can be done directly from the hub. This is helpful if you're running into issues with inclusion. To exclude a device, start the exclusion process on your hub and press the Configuration / Favorites Button (C) 3x rapidly. The LED Bar (D) will start pulsing blue and if successful, it will flash green. If unsuccessful it will flash red.

Page intentionally left blank.

**Product & Contact Info.**

# Product & Contact Info Notes

As mentioned in the beginning of the manual, we're all smart home owners ourselves and have an amazing community of people who are eager to help and share their setups.

If you ever run into any issues, please do not hesitate to submit a ticket, or post in the community. We'd love to hear from you.

**Community Link:** [inov.li/community](https://inov.li/community)

**Submit a Ticket:** [inov.li/support](https://inov.li/support)

Thanks again for your support and we look forward to helping you get the most out of our smart home!



# FCC/IC Statements

**FCC Caution:** Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received including interference that may cause undesired operation.

**NOTE:** This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency

# FCC/IC Statements (Cont.)

energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

Reorient or relocate the receiving antenna, increase the separation between the equipment and receiver, connect the equipment into an outlet on a circuit different from that to which the receiver is connected or consult the dealer or an experienced radio/TV technician for help. This equipment should be installed and

operated with minimum distance 8in (20cm) between the radiator and your body.

**IC Caution:** This device complies with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

**DECLARATION DE CONFORMITE D'INDUSTRIE CANADA:** Ce périphérique a été testé et reconnu conforme aux limites spécifiées dans RSS-210. Son utilisation est soumise aux deux conditions suivantes: (1) il ne doit pas provoquer d'interférences gênantes et (2) il doit tolérer les interférences, notamment celles susceptibles d'en perturber le fonctionnement.

# Product Info

Name: Smart Dimmer Switch

SKU #: LZW31-SN

Power: 120V AC, 60Hz

Signal (Frequency): 908.42 MHz

Operating Temperature Range: 32-104 °F (0-40 °C)

Maximum Load (Watts): 400W Single-Gang, 300W Double-Gang, 200W Triple-Gang Incandescent, 300W LED, 150W CFL

Not rated for inductive loads or fans.

Range: Up to 100 meters line of sight between the Wireless Controller (HUB) and the closest Z-Wave Repeater.

Certifications: UL Listed (#E508406), FCC/IC & Z-Wave Plus Certified

For indoor use. Specifications subject to change without notice due to continuing product improvement.

# Company Info / Warranty

If you run into any issues, feel free to reach out to us at: [contact@inovelli.com](mailto:contact@inovelli.com). We typically answer tickets within 24-48 hours and are staffed by actual smart home owners.

All Inovelli products come with a one (1) year warranty (defined as 365 days). This warranty protects you from breakdowns in the material or workmanship under normal use. This warranty is limited in a couple areas. Purchases must be made from Inovelli or an authorized reseller. The product should be used in the manner directed in the instructions. The product must only be used and/or installed in the United States or Canada.

For full warranty info, please visit: [inov.li/warranty](http://inov.li/warranty)

# Project Lights Out

Project, "Lights Out" started as a rally cry that we were going to turn the lights out on other smart home switches with this product because it would be that good. Our approach to building products is that we want something we'd put in our own home (we're all smart home owners) and we want to build our products with you taking the ride with us. That is, these are community built products in which 100's, if not 1000's of people outside of Inovelli have contributed to.

This switch is our first opportunity to build from scratch a true community as assembled product from both a hardware and firmware side. To see the project come to life, feel free to visit the project page: [inov.li/lightsout](http://inov.li/lightsout)

**Thank You.**

inovelli®